

# CLADBOY CB<sub>4</sub>

## THE ALLROUNDER



VACUUM LIFTING DEVICE FOR  
ROOF- AND WALL PANELS



Configuration for roof panels



# CLADBOY CB4

THE ALLROUNDER

LIFTING EYE

CONFIGURATION FOR WALL PANELS

SOLID GRIPS

STORAGE BOX

Connection cable  
battery charger

VACUUM GAUGE

Red-green indication

FILTER

QUICK COUPLINGS

To connect vacuum hoses

LOCKING PIN

To lock the main traverse  
in the end position

INDICATION

Battery charging level

CONTROL

Suction and release  
with safety latch

CASING

For the electric components

## POSSIBILITIES

With the option of various suction pads and extension kits, the machine is unique flexible and versatile and can be used for many applications such as:

- Horizontal wall panels
- Vertical wall panels
- Flat or inclined roof panels

The standard suction pads are suitable for all commonly used sandwich roof and wall panels. For other profiles such as corrugated and roof tile profile, special suction pads are available.

## SAFETY FEATURES

- Clear audible low vacuum warning
- Large vacuum buffer tank
- Low battery warning
- Secondary safety device

## SPECIFICATION

- Lifting capacity max. 800 kg  
(depends on applied suction pads)
- Machine weight min. 125 kg  
(depends on used configuration)

SUCTION PADS  
With exchangeable seals

MAIN TRAVERSE  
90° rotateable

COMPACT AND DURABLE  
POWERED BY INTERNAL  
RE-CHARGEABLE BATTERY



EASY TO TRANSPORT

Complies with European standard EN 13155

