

CLADBOY CB₅

THE ALLROUNDER



VACUUM LIFTING DEVICE FOR
ROOF- AND WALL PANELS



Configuration for roof panels



CLADBOY CB5

THE ALLROUNDER

CONFIGURATION FOR WALL PANELS

LIFTING EYE

SOLID GRIPS

STORAGE BOX

Connection cable
battery charger

VACUUM GAUGE

Red-green indication

QUICK COUPLINGS

To connect vacuum hoses

LOCKING PIN

To lock the main traverse
in the end position

INDICATION

Battery charging level

CONTROL

Suction and release
with safety latch

CASING

For the electric components

FILTER

POSSIBILITIES

With the option of various suction pads and extension kits, the machine is unique flexible and versatile and can be used for many applications such as:

- Horizontal wall panels
- Vertical wall panels
- Flat or inclined roof panels

The standard suction pads are suitable for all commonly used sandwich roof and wall panels. For other profiles such as corrugated and roof tile profile, special suction pads are available.

SAFETY FEATURES

- Dual vacuum circuit
- Clear audible low vacuum warning
- Large vacuum buffer tank
- Low battery warning

SPECIFICATION

- Lifting capacity max. 800 kg
(depends on applied suction pads)
- Machine weight min. 150kg
(depends on used configuration)



SUCTION PADS

With exchangeable seals

MAIN TRAVERSE

90° rotateable



EASY TO TRANSPORT

COMPACT AND DURABLE
POWERED BY INTERNAL
RE-CHARGEABLE BATTERY

Complies with European standard EN 13155

