

NEW NEW NEW



SMARTLIFT



SL409 HLE RT Outdoor

## SL409 HLE RT OUTDOOR

LIFTS UP TO 430 KG / 950 LBS.

The new SL409 HLE RT is efficient and hard working. It saves you the cost of extra hands for mounting of elements like glass, windows, granite, marble, and steel and it never needs a day off. The increasing demand for triple pane windows and other energy-saving building elements triggers much more heavy lifting. The compact and ruggedized design gets the job done.

### VACUUM SYSTEM IS REMOTELY CONTROLLED

Stay focused on the mounting and release the vacuum with the remote control

### SPEEDY TILTING

The increased speed of tilting easily gets you in position for the final adjustments

### NEW GEL BATTERY PACK

The SL409 HLE RT comes with a gel battery pack for general availability and longer lifetime

### SAVE POSITION FOR REPEATED MOUNTING

Save a mounting position on the remote control and retrieve it for repeated mounting.

### X/Y MOVEMENT

The straight movement is easy to control and prevents damages from accidentally bumping something in the normal curved movement

### THEFT PROTECTION, GEOFENCING AND REMOTE DIAGNOSTICS

The built-in Trackunit IoT device is safeguarding against theft and breakdowns

### SAFETY FEATURES

The emergency stop is easy to reach and the lights indicate correct operation and errors like low vacuum pressure and other system errors



REACH OF EXTENDED ARM  
**UP TO 175 CM** /68 IN.



LIFTING HEIGHT  
**UP TO 370 CM** /145 IN.



**STRONG, ROBUST  
AND FLEXIBLE**

# SL409 HLE RT OUTDOOR

## TECHNICAL SPECIFICATIONS

Model	SL409 HLE RT Outdoor
Lifting cap. arm in/out	430/90 kg - 950/200 lbs
Lifting height	3700 mm/145 in
Extension of arm	600+600 mm/24 + 24 in
Tip from horizontal	45° back / 90° fwd
Side shift	100 mm / 4 in
Charging voltage	230 V / 110 V
Charging time	Approx. 8 hrs
Running period	Up to 10 hrs
Front-wheel drive	1500 W AC
Suction pads	4 x Ø300 mm / 4 x Ø12 in
Width	820 mm / 32 in
Curb weight	730 kg / 1600 lbs
Class	IP 65

