ACCESSORIES





TIRES AND RAMPS

	Name	Description	SL 208 Indoor	SL 280 Indoor	SL 380 Indoor	SL 580 Indoor	SL 408 Outdoor	SL 408 Outdoor HL	SL 608 Outdoor	SL 608 Outdoor HL/HLE	SL 608 Outdoor HL RT/HLE RI	SL 808 Outdoor	SL 1008 Outdoor
	Puncture proof tires	Foam-filled puncture proof tires for the outdoor line.					•	STANDARD	•	STANDARD	STANDARD	STANDARD	STANDARD
	White non- marking tires	Does not leave marks on your floor. For indoor use.	•	•	•	•	•	•	•	•	•	•	•
0	3 Wheel cover	Cover for non-marking driving indoor.					•	•	•	•	•	•	•
Voto	Transport ramp	Aluminium ramp - small. Ramp measures 2000 x 650 mm.		•	•								
	Transport ramp	Aluminium ramp - medium. Ramp measures 2500 x 850 mm.	•	•	•	•	•	•	•	•	•		
	6 Transport ramp	Aluminium ramp - large. Ramp measures 3000 x 590 mm.										•	•
	7 Alu Transport- palette	Transport palette/ramp for transportation of your Smart Lift. Ramp measures 900 x 2000 mm.	•	•	•	•	•	•	•	•	•		

	SI	JCTIO								Щ	/HLE RT				
	Name		Description	SL 208 Indoor	SL 280 Indoor	SL 380 Indoor	SL 580 Indoor	SL 408 Outdoor	SL 408 Outdoor HL	SL 608 Outdoor	SL 608 Outdoor HL/HLE	SL 608 Outdoor HL RT/HLE	SL 808 Outdoor	SL 1008 Outdoor	SL 400
	8	SGF Suction pad Ø125 - Ø400 mm	Standard suction pad especially suited for glass with a completely smooth surface. Max. load capacity at 2 x 2 pcs. from 75 - 650 kg. 1 pc.		•	•	•	•	•	•	•	•	•	•	•
	9	SPU Suction pad Ø100 - Ø400 mm	Suction pad suitable for glass with a smooth surface, but can also absorb minor irregularities. Replace- able rubber. Max. load capacity at 2 x 2 pcs. from 25 - 580 kg. 1 pc.	•	•	•	•	•	•	•	•	•	•	-	•
	10	SPK Suction pad Ø55 - Ø250 mm	Suitable for Paroc-subjects and port elements that have a surface that is not completely smooth. Replaceable rubber. Max. load capacity at 2 x 2 pcs. from 15 - 250 kg. 1 pc.	•	•	-	•	•	•	•	•	•	•	-	•
0	11	FSGPL Bellow Suction pad Ø100 – Ø250 mm	Especially suitable for curved glass with a smooth surface. Can be combined with Flexolink. Max. load capacity at 2 x 2 pcs. from 20 - 240 kg. 1 pc.	•	•	•	•	•	•	•	•	•	•	-	•
	12	SPLO Suction pad 370x80mm	Oval suction pad suitable for handling thin sheet metals and other light materials. Multiple pads are often used. Max. load capacity at 2 x 2 pcs. 127 kg.	•	•	•	•	•	•	•	•	•	•	•	•
	13	Oval suction pad 500x180mm	Large oval suction pad designed for handling curved items with a radius down to 1100mm, if combined with Flexolink and Double suction bracket flex. Max. load cap. 2 x 2 pcs. 400 kg.	•	•	•	•	•	•	•	•	•	•	•	•
SMARTLET	14	Protection cover	Type 200, 250, 300, or 400. For suction pad Ø200, Ø250, Ø300, or Ø400 mm. 1 pc.	•	•	•	•	•	•	•	•	•	•	-	•
	15	Flexolink	Flexible connectors for curved panes of glass. No. 010398 for suction pad up to Ø300mm - up to 12° curve. No. 010571 for suction pad larger than Ø300 mm - up to 9° curve. 1 pc.	•	•	•	•	•	•	•	•	•	•	-	•
*	16	Flex extender	Adjustable bracket with 200 mm adjustment for suction pads. 1 pc.	•	•	•	•	•	•	•	•	•	•	•	
0*	17	Double flex extender	Ajustable bracket with 200 adjustment for SPLO and Oval suction pads. 1 pc.	•	•	•	•	•	•	•	•	•	•	•	

EXTENDERS						SL 380 Indoor	SL 580 Indoor	SL 408 Outdoor	SL 408 Outdoor HL	SL 608 Outdoor	SL 608 Outdoor HL/HLE	SL 608 Outdoor HL RT/HLE RT	SL 808 Outdoor	SL 1008 Outdoor	SL 400
ý,	Name	<u>)</u>	Description	SL 208 Indoor	SL 280 Indoor	O	o)	O)	O)	(S)	()	(r)	o)	(C)	
	18	Extender type +105 mm	Suction pad extender. Intended for loads with various levels. 1 pc.	•	•	•	•	•	•	•	•	•	•	•	
	19	Extender type +250 mm	Suction pad extender. Intended for loads at with various levels. 1 pc.		•	•		•	•	•		•	•	•	
	20	Profile tube 40 x 40 mm	Extension for traverse L = 50 cm.		•	•		•	•						
	21	Profile tube 50 x 50 mm	Extension for yoke L = 50 cm.		•	•	•	•	•		•	•	•	•	
	22	Profile tube 60 x 60 mm	Extension for yoke L = 50 cm.				•			•	•		•	•	



	M	ISCEL	SL 208 Indoor	SL 280 Indoor	SL 380 Indoor	SL 580 Indoor	SL 408 Outdoor	SL 408 Outdoor HL	SL 608 Outdoor	SL 608 Outdoor HL/HLE	SL 608 Outdoor HL RT/HLE RT	SL 808 Outdoor	SL 1008 Outdoor	SL 400	
	Name	è	Description	SL 2	SL 2	SL 3	SL 5	SL 4	SL 4	SL 6	SL 6	SL 6	SL 8	SL 1	SL 4
	23	Pallet fork	Type 300, 500, 500 RT, or 700 Smartlift pallet fork with a max. load capacity of up to 300, 500 or 700 kg.	•	•	•	•	•	•		•	•	•	•	
000	24	Lifting hook	Type 400, 600, 600 RT, or 800 Strong lifting hook with a max. load capacity of up to 400, 600 or 800 kg.	•	-	•	•	•	•	•	•	•	•		
Sh	25	Electric key switch			•	•	•	•	•	•	•	•	•	•	
	26	Wooden crate	011760: 1850 x 1050 x 1500 mm 011761: 2150 x 1050 x 1500 mm 011762: 2900 x 1200 x 1700 mm 011791: 1300 x 1200 x 1300 mm (internal dimensions)	•	•			•	•		•		•	•	
*	27	Rotatable traverse	A rotary traverse which allows you to align suction pads in a row or place them in other ways. Suitable for use with narrow or e.g. triangular loads. 1 pc.				•	•	•		•	•	•	•	
N. C.	28	Pivoting traverse	E.g. for curved glass. Traverse measures 1600 mm. 1 pc.	•	•	•	•	•			•		•		
65	29	Special colour	Select one or more special RAL colours.	+ delivery time	+ delivery time	+ delivery time	+ delivery time	+ delivery time	+ delivery time	+ delivery time					

ELECTRICAL ACCESSORIES

	Name		Description	SL 208 Indoor	SL 280 Indoor	SL 380 Indoor	SL 580 Indoor	SL 408 Outdoor	SL 408 Outdoor HL	SL 608 Outdoor	SL 608 Outdoor HL/HLE	SL 608 Outdoor HL RT/HLE F	SL 808 Outdoor	SL 1008 Outdoor	SL 400
	30	Cordless remote control Pocket	Cordless remote control for selected SmartLift models. Can replace the cable remote control. (Factory option only)		•		•	•	•	•					
	31	Cordless remote control Pocket	Cordless remote control for selected Smartlift models. Add three optional extra functions. Can be combined with eletric rotation or vacuum control. (Factory option only)	-	•	•	•	•	•	•	•	•			
ЕСАНИЕСО	32	Battery for radio controller	When you have an extra battery, you can operate the controller non-stop without breaks for recharging.											•	•
	33	Battery charger											•	•	•
FR	34	Transformer for the charging unit	Adaptor for the charger to the current network. (110-240 V, 50-60 Hz). (For Radio Controller)										•	-	•
	35	Radio controller													•
	36	Lithium battery	When you have an extra battery, you can operate Sky Lifter nonstop without breaks for recharging.												•
	37	Charger for lithium battery	Charger unit for battery. (110-240 V, 50-60 Hz).												•



MOUNTING EQUIPMENT FOR SL400

	Name		Description	SL 400 S
	38	Mounting bracket/adapter Manitou	Mounting bracket/adapter – to install SL400 on a Manitou.	-
	39	Quick-change fitting M2016	Mounting set for SL400. Parts with no suspended attachment to the parent machine.	-
D	40	Bearing plate Quick-Change M2016	Pre-drilled plate for SL400. Parts with no suspended attachment to the parent machine. State serial no. of machine when ordering Quick-Change and hole plates.	•
	41	Perforated plate	Pre-drilled perforated plate for mounting on SL400. Part without anchoring for the parent machine.	•
M	42	JCB Quick- Change M2016	Quick-change for mounting SL400 on machines with Q-fit changer. Can be used for Quick-Change fitting Sky Lifter M2016.	-

GET MORE OUT OF YOUR SMARTLIFT

There is a wide range of accessories available for your Smartlift. Everything from pallet forks, ramps, hooks and suction pads for various types of surfaces and shapes are just some of the possibilities. **Smartlift – the safe choice!**



CONTACT US

N.A. Christensensvej 39 DK - 7900 Nykøbing Mors Denmark

T +45 97 72 29 11

E smart@smartlift.com

W smartlift.com